





RESIDENTIAL SECTIONAL GARAGE DOOR OPENER MYQ & BATTERY BACKUP COMPATIBLE

POWERFUL LED LIGHTING
Illuminate your garage
corner-to-corner.

MYQ COMPATIBLE
Opener is myQ compatible with
additional purchase of Safety IR
Beams & myQ Gateway.¹

BATTERY BACKUP COMPATIBLE
Opener is Battery Backup compatible
with additional purchase of Battery
Backup accessory.

Compliant to Australian and New Zealand
Standard AS/NZS 60335-2-95

SMART



MYQ COMPATIBLE TECHNOLOGY lets users create schedules, monitor, receive alerts and control the garage door opener away from home.¹



 $\textbf{SOFT-START AND SOFT-STOP} \ \text{for smooth operation}.$

QUIET & RELIABLE



7-YEAR WARRANTY



 ${\bf QUIET\ DC\ MOTOR}$ eliminates noise and vibrations through the ceiling and provide smooth operation.



HEAVY-LIFTING POWER operates doors up to $150 \ kg$ / $286 \ kg.^3$



BATTERY BACKUP ensures access even when the power is out.²

SAFE & SECURE



 $\textbf{SECURITY+ 2.0} \$ \ \text{sends a new code with every remote click}.$



PREMIUM AUTOMATIC SAFETY REVERSE function will allow your garage door to stop and reverse automatically if obstructed going down or stop going up.



TIMER-TO-CLOSE automatically closes the door after a pre-set amount of time.⁴



IMPROVED TRANSMITTER RANGE has up to 18% better range meaning you can start opening your garage door sooner.⁵



AUTOMATIC FORCE SENSING monitors and adjusts the force needed to open your garage with each operation.



MANUAL RELEASE CORD allows you to open your garage door whenever needed.

ACCESSORIES INCLUDED

E960M

E138M

M828AU774

827 AU

E840M

E943M



2 PREMIUM+ REMOTES

Each button is independently programmable and backed by Security+ 2.0 technology.



TWO BUTTON WIRELESS WALL BUTTON

Controls up to two garage door openers and is backed by Security+2.0 technology.





MYQ CONNECTIVITY BUNDLE

Add monitoring and control away from home. Includes myQ Gateway and The Protector SystemTM (Safety IR Beams).



MYQ REMOTE LED LIGHT Ultra-bright LED light designed to illuminate your garage or workspace. Controlled by a garage door opener, remote control or myQ app.



BATTERY BACKUP

Get in and out when the power's out with Battery Backup.



WIRELESS SECURITY KEYPAD

Convenient and safe access to your garage without using a remote control or key.



SINGLE BUTTON REMOTE CONTROL WITH CAR VISOR CLIP Easily attaches to

your car visor to control one garage door. Backed by Security+ 2.0 technology.



THREE BUTTON REMOTE CONTROL WITH CAR VISOR CLIP Easily attaches to your car visor to control up to three garage

your car visor to control up to three garage doors. Backed by Security+ 2.0 technology.

gomerlin.com.au **■** gomerlin.co.nz

Additional purchase of Merlin myQ Gateway and Safety IR Beam accessories required to enable myQ functionality. Visit gomerlin.com.au or gomerlin.com.au for further information. *Additional purchase of Merlin Battery Backup functionality. Visit gomerlin.com.au or gomerlin.com.au for further information. *286 kg door rating is based on having installation of Safety IR Beams. *Safety IR Beams must be installed to enable the use of Timer-to-Close. See User Guide for additional information. Smartphone not included. *When compared to other available Merlin products.

Commander Extreme

DESIGNED FOR EXTREME WEATHER CONDITIONS & HEAVY CUSTOM DOORS

MS125MYQ









Merlin

RESIDENTIAL SECTIONAL GARAGE DOOR OPENER

MYQ & BATTERY BACKUP COMPATIBLE

GARAGE DOOR OPENER IS COMPATIBLE WITH my Q.

Additional purchase of The Protector System™ and myQ Gateway is required

APP AVAILABLE ON:






- Monitor and control your garage door away from home through the Merlin myQ app.
- Peace of mind knowing if your garage door is open or closed anywhere and any time.
- Receive real time alerts and notifications so you know when the garage door is opened or closed by loved ones.
- Pre-set times to automatically close your
- See history records of your garage door open and close periods.

garage door at any time.

- Protect your loved ones and belongings with The Protector System[™] (Safety IR Beams).
- Compatible Merlin myQ app available for smart devices including Apple Watch.

TYPICAL INSTALLATION - SECTIONAL DOORS



- · Maximum lifting under spring tensions 20 kg
- · Suitable for steel and timber spring balanced doors
- Total door area: 20m²
- Single dwelling, max door weight up to 150 kg / 286 kg⁽³⁾







SECURITY+ 2.0®

- Encrypted rolling code across multiple frequencies.
- Security+ 2.0® technology virtually eliminates interference.



RADIO

- Provides 2-way communication from rolling door opener and accessories.
- · Receiver with 64 memory registers.



LIGHTING: LED LIGHTING

- LED light turns on with activation.
- Turns off 2.5 minutes after operation.

STANDARD SPECIFICATIONS

- Input voltage: 240V AC
- Rated door areas up to: 20m²
- Max door height: 3.5m
- Max door weight: 150 kg / 286 kg⁽³⁾
- Max peak pulling force: 1200N
- Max lift under spring tension: 20 kg
- Radio frequency: 433.30, 433.92, 434.54 MHz with Security+ 2.0 technology
- Minimum headroom required: 30mm
- C-rail with chain drive
- 24C DV motor with thermal overload protection
- Lighting: LED Lighting
- Garage Door Opener Capacity of up to 64 memory registers
- Compatible with myQ technology²





AUSTRALIA

Chamberlain Australia Pty Ltd PO Box 1446 Lane Cove NSW 1595 Australia

gomerlin.com.au 1800 638 234

NEW ZEALAND

Chamberlain New Zealand Ltd PO Box 100-221 North Shore Auckland 0745 New Zealand

gomerlin.co.nz 0800 653 667

Designed & Engineered in Australia

© Chamberlain Group 2019. All Rights Reserved. TM Trademark of The Chamberlain Group, Inc. ® Registered Trademark of the Chamberlain Group.